

选型表SELECTION TABLE 6.3kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃	VDE CCS ABS BV GL LRS DNV RINa				输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
1000 r/min (6-pole)												
1875	1763	1631	1500		ZFC7 453-6P	10800	170	1500	172	96.1	97.1	3000X1650X1950
2500	2350	2175	2000		454-6P	11600	200	2000	229	96.6	97.5	3130X1650X1950
3125	2938	2719	2500		ZFC7 503-6P	14950	350	2500	287	96.4	97.3	3261X1900X2270
4000	3760	3480	3200		504-6P	16250	475	3200	366	96.6	97.5	3461X1900X2270
5000	4700	4350	4000		505-6P	17300	550	4000	458	96.9	97.7	3561X1900X2270
6250	5875	5438	5000		506-6P	18650	680	5000	573	97.1	97.8	3791X1900X2270
7500	7050	6525	6000		ZFC7 563-6P	23900	1250	6000	687	97.1	97.8	3710X2140X2540
8750	8225	7613	7000		564-6P	25200	1420	7000	802	97.2	97.9	3830X2140X2540
10000	9400	8700	8000		565-6P	26950	1600	8000	916	97.3	98.0	4230X2140X2540
11250	10575	9788	9000		ZFC7 633-6P	38200	2690	9000	1031	97.1	97.8	3910X2600X2960
12500	11750	10875	10000		634-6P	40200	3150	10000	1145	97.2	97.8	4050X2600X2960

选型表SELECTION TABLE 6.3kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ... °C RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ... °C												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
°C	°C	°C	°C	输出率 POWER OUTPUT				额定电流 RATED CURRENT	效率 EFFICIENCY			
40	45	50	55	VDE	kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm	
—	—	45	50	CCS								
—	—	—	50	ABS								
—	40	45	50	BV								
40	45	—	—	GL								
—	40	45	50	LRS								
35	—	45	—	DNV								
—	45	50	—	RINa								
kVA	kVA	kVA	kVA									
750 r/min (8-pole)												
1875	1763	1631	1500		ZFC7 503-8P	13550	360	1500	172	95.7	96.9	2870X1900X2270
2500	2350	2175	2000		504-8P	14550	490	2000	229	96.2	97.2	3210X1900X2270
3125	2938	2719	2500		505-8P	15500	600	2500	287	96.5	97.4	3340X1900X2270
4000	3760	3480	3200		506-8P	16850	740	3200	366	96.8	97.6	3520X1900X2270
5000	4700	4350	4000		508-8P	19500	850	4000	458	97.0	97.8	3610X1900X2270
6250	5875	5438	5000		ZFC7 564-8P	22700	1690	5000	573	97.0	97.7	3660X2140X2540
7500	7050	6525	6000		565-8P	24150	1920	6000	687	97.2	97.9	3960X2140X2540
8750	8225	7613	7000		567-8P	25500	2250	7000	802	97.4	97.9	4160X2140X2540
10000	9400	8700	8000		ZFC7 634-8P	37210	4150	8000	916	97.2	97.9	3960X2600X2960

选型表SELECTION TABLE 6.3kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃					输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
40	45	50	55	VDE								
—	—	45	50	CCS								
—	—	—	50	ABS								
—	40	45	50	BV								
40	45	—	—	GL								
—	40	45	50	LRS								
35	—	45	—	DNV								
—	45	50	—	RINa								
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
600 r/min (10-pole)												
1563	1469	1360	1250		ZFC7 504-10P	13500	450	1250	143	95.3	96.5	2840X1900X2270
1875	1763	1631	1500		505-10P	14050	530	1500	172	95.7	96.8	3100X1900X2270
2500	2350	2175	2000		506-10P	15100	695	2000	229	96.1	97.1	3260X1900X2270
3125	2938	2719	2500		ZFC7 563-10P	21170	1230	2500	287	96.2	97.2	3190X2140X2540
4000	3760	3480	3200		564-10P	22500	1715	3200	366	96.4	97.3	3450X2140X2540
5000	4700	4350	4000		565-10P	23650	2030	4000	458	96.7	97.6	3590X2140X2540
6250	5875	5438	5000		ZFC7 633-10P	32800	4210	5000	573	96.7	97.5	3750X2600X2960
7500	7050	6525	6000		634-10P	34500	5170	6000	687	96.9	97.7	3900X2600X2960

选型表SELECTION TABLE 6.3kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃	输出率 POWER OUTPUT				额定电流 RATED CURRENT	效率 EFFICIENCY			
40	45	50	55	VDE		kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
—	—	45	50	CCS								
—	—	—	50	ABS								
—	40	45	50	BV								
40	45	—	—	GL								
—	40	45	50	LRS								
35	—	45	—	DNV								
—	45	50	—	RINa								
500 r/min (12-pole)												
1563	1469	1360	1250		ZFC7 505-12P	13900	597	1250	143	95.1	96.3	2940X1900X2270
1875	1763	1631	1500		506-12P	14500	690	1500	172	95.4	96.5	3160X1900X2270
2500	2350	2175	2000		ZFC7 563-12P	21500	1200	2000	229	95.7	96.9	3190X2140X2540
3125	2938	2719	2500		564-12P	22000	1580	2500	287	96.1	97.1	3290X2140X2540
4000	3760	3480	3200		565-12P	23500	1900	3200	366	96.3	97.2	3530X2140X2540
5000	4700	4350	4000		ZFC7 633-12P	31000	3400	4000	458	96.5	97.3	3720X2600X2960
6250	5875	5438	5000		634-12P	33500	4500	5000	573	96.6	97.4	3870X2600X2960
7500	7050	6525	6000		635-12P	35000	5470	6000	687	96.8	97.6	4020X2600X2960