

选型表SELECTION TABLE 10.5kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃	VDE CCS ABS BV GL LRS DNV RINa				输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
1000 r/min (6-pole)												
1875	1763	1631	1500		ZFC7 455-6P	11000	180	1500	103	95.9	96.9	3190X1650X1950
2500	2350	2175	2000		ZFC7 504-6P	14200	330	2000	137	95.6	96.7	3430X1900X2270
3125	2938	2719	2500		505-6P	15200	410	2500	172	96.0	97.0	3560X1900X2270
4000	3760	3480	3200		506-6P	16400	500	3200	220	96.4	97.3	3700X1900X2270
5000	4700	4350	4000		507-6P	18300	660	4000	274	96.6	97.4	4020X1900X2270
6250	5875	5438	5000		ZFC7 564-6P	23200	1140	5000	344	96.6	97.4	3750X2140X2540
7500	7050	6525	6000		565-6P	24900	1360	6000	411	96.9	97.6	3910X2140X2540
8750	8225	7613	7000		566-6P	26050	1480	7000	481	97.1	97.8	4000X2140X2540
10000	9400	8700	8000		ZFC7 634-6P	37200	2630	8000	548	96.8	97.6	4140X2600X2960
11250	10575	9788	9000		635-6P	38400	2840	9000	618	97.0	97.7	4210X2600X2960

选型表SELECTION TABLE 10.5kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃	船级社				输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
40	45	50	55	VDE								
—	—	45	50	CCS								
—	—	—	50	ABS								
—	40	45	50	BV								
40	45	—	—	GL								
—	40	45	50	LRS								
35	—	45	—	DNV								
—	45	50	—	RINa								
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
750 r/min (8-pole)												
1875	1763	1631	1500		ZFC7 505-8P	13900	430	1500	103	95.3	96.5	3130X1900X2270
2500	2350	2175	2000		506-8P	14900	550	2000	137	95.8	96.9	3460X1900X2270
3125	2938	2719	2500		507-8P	16000	650	2500	172	96.3	97.2	3580X1900X2270
4000	3760	3480	3200		ZFC7 564-8P	20000	1200	3200	220	96.1	97.1	3435X2140X2540
5000	4700	4350	4000		565-8P	22000	1580	4000	274	96.4	97.3	3695X2140X2540
6250	5875	5438	5000		566-8P	23700	1840	5000	344	96.8	97.6	3835X2140X2540
7500	7050	6525	6000		ZFC7 634-8P	35200	3380	6000	411	96.7	97.5	3980X2600X2960
8750	8225	7613	7000		635-8P	36800	3980	7000	481	96.8	97.6	4110X2600X2960

选型表SELECTION TABLE 10.5kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ...°C RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...°C												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
°C	°C	°C	°C					输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
40	45	50	55	VDE		kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
—	—	45	50	CCS								
—	—	—	50	ABS								
—	40	45	50	BV								
40	45	—	—	GL								
—	40	45	50	LRS								
—	—	45	—	DNV								
35	—	45	—	RINa								
—	45	50	—									
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
600 r/min (10-pole)												
1563	1469	1360	1250		ZFC7 506-10P	13750	500	1250	86	95.1	96.3	3080X1900X2270
1875	1763	1631	1500		507-10P	14250	600	1500	103	95.4	96.6	3330X1900X2270
2500	2350	2175	2000		ZFC7 564-10P	20100	1200	2000	137	95.5	96.6	3290X2140X2540
3125	2938	2719	2500		565-10P	21650	1520	2500	172	95.8	96.9	3430X2140X2540
4000	3760	3480	3200		566-10P	22950	1850	3200	220	96.3	97.2	3630X2140X2540
5000	4700	4350	4000		567-10P	25500	2100	4000	274	96.4	97.3	3780X2140X2540
6250	5875	5438	5000		ZFC7 635-10P	34500	4660	5000	344	96.5	97.4	3990X2600X2960
7500	7050	6525	6000		636-10P	36000	5300	6000	411	96.7	97.7	4190X2600X2960

选型表SELECTION TABLE 10.5kV/ 50Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃	VDE — — — 40 — 35 —				45 — — 40 45 — 45 50	50 45 — — — — —	55 50 50 — — — —	输出功率 POWER OUTPUT	
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
500 r/min (12-pole)												
1563	1469	1360	1250		ZFC7 507-12P	14500	627	1250	86	94.9	96.2	3200X1900X2270
1875	1763	1631	1500		508-12P	15000	720	1500	103	95.1	96.3	3450X1900X2270
2500	2350	2175	2000		ZFC7 565-12P	22500	1500	2000	137	95.3	96.5	3450X2140X2540
3125	2938	2719	2500		566-12P	23000	1800	2500	172	95.6	96.7	3580X2140X2540
4000	3760	3480	3200		ZFC7 634-12P	31000	3500	3200	220	95.8	96.9	3900X2600X2960
5000	4700	4350	4000		635-12P	33000	4000	4000	274	96.2	97.1	4000X2600X2960
6250	5875	5438	5000		636-12P	35500	5000	5000	344	96.3	97.2	4130X2600X2960