

选型表SELECTION TABLE 11kV/ 60Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃	输出 功率 POWER OUTPUT				额定电 流 RATED CURRENT	效率 EFFICIENCY			
40 — — — 40 — 35 —	45 — — 40 45 40 — 45	50 45 — 45 — 45 50	55 50 50 50 — — —	VDE CCS ABS BV GL LRS DNV RINa				kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	
kVA	kVA	kVA	kVA		kg	kgm ²					mm	
1200 r/min (6-pole)												
1875	1763	1631	1500		ZFC7 454-6P	10500	150	1500	98	95.4	96.3	3100X1650X1950
2500	2350	2175	2000		ZFC7 503-6P	14000	290	2000	131	94.9	95.8	3370X1900X2270
3125	2938	2719	2500		504-6P	15000	370	2500	164	95.4	96.2	3500X1900X2270
4000	3760	3480	3200		505-6P	16200	470	3200	210	95.8	96.4	3660X1900X2270
5000	4700	4350	4000		506-6P	17500	580	4000	262	96.1	96.7	3900X1900X2270
6250	5875	5438	5000		ZFC7 563-6P	22200	980	5000	328	96.0	96.6	3850X2140X2540
7500	7050	6525	6000		564-6P	23500	1130	6000	394	96.3	96.9	3960X2140X2540
8750	8225	7613	7000		565-6P	25000	1300	7000	459	96.6	97.1	4090X2140X2540
10000	9400	8700	8000		ZFC7 633-6P	35800	2160	8000	525	96.3	96.7	4000X2600X2960
11250	10575	9788	9000		634-6P	37500	2510	9000	590	96.4	96.8	4110X2600X2960

选型表SELECTION TABLE 11kV/ 60Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃					输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
40	45	50	55	VDE		kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
—	—	45	50	CCS								
—	—	—	50	ABS								
—	40	45	50	BV								
40	45	—	—	GL								
—	40	45	50	LRS								
35	—	45	—	DNV								
—	45	50	—	RINa								
900 r/min (8-pole)												
1875	1763	1631	1500		ZFC7 504-8P	13500	355	1500	98	94.7	95.8	3050X1900X2270
2500	2350	2175	2000		505-8P	15000	500	2000	131	95.2	96.1	3410X1900X2270
3125	2938	2719	2500		506-8P	16500	595	2500	164	95.7	96.5	3530X1900X2270
4000	3760	3480	3200		ZFC7 563-8P	19400	1060	3200	210	95.6	96.4	3365X2140X2540
5000	4700	4350	4000		564-8P	21000	1350	4000	262	95.9	96.6	3575X2140X2540
6250	5875	5438	5000		565-8P	23000	1515	5000	328	96.4	97.0	3715X2140X2540
7500	7050	6525	6000		ZFC7 633-8P	34000	2940	6000	394	96.1	96.6	3880X2600X2960
8750	8225	7613	7000		634-8P	35500	3550	7000	459	96.2	96.8	4010X2600X2960

选型表SELECTION TABLE 11kV/ 60Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃	船级社				输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
40	45	50	55	VDE								
—	—	45	50	CCS								
—	—	—	50	ABS								
—	40	45	50	BV								
40	45	—	—	GL								
—	40	45	50	LRS								
35	—	45	—	DNV								
—	45	50	—	RINa								
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
720 r/min (10-pole)												
1563	1469	1360	1250		ZFC7 505-10P	13550	460	1250	82	94.3	95.4	3000X1900X2270
1875	1763	1631	1500		506-10P	14150	560	1500	98	94.7	95.6	3180X1900X2270
2500	2350	2175	2000		ZFC7 563-10P	18500	1040	2000	131	94.9	95.9	3220X2140X2540
3125	2938	2719	2500		564-10P	20600	1370	2500	164	95.3	96.2	3360X2140X2540
4000	3760	3480	3200		565-10P	21900	1630	3200	210	95.8	96.5	3530X2140X2540
5000	4700	4350	4000		566-10P	24500	1900	4000	262	95.4	96.2	3690X2140X2540
6250	5875	5438	5000		ZFC7 634-10P	33100	4120	5000	328	96.0	96.7	3900X2600X2960
7500	7050	6525	6000		635-10P	34600	4780	6000	394	96.3	97.0	4100X2600X2960

选型表SELECTION TABLE 11kV/ 60Hz F/F

额定输出容量和冷却介质温度 (CT) ...℃ RATED OUTPUT POWER AND COOLANT TEMPERATURE (CT) ...℃												参考外形尺寸 OVERALL DIMENSION
1	2	3	4	船级社	型号 MODEL	净重 NET WEIGHT	转动惯量 MOMENT OF INERTIA	与本表第一栏的额定输出容量对应的性能参数 PERFORMANCE DATA AT RATED OUTPUT ACCORDING TO COLUMN 1				长X宽X高 LXBXH
℃	℃	℃	℃					输出功率 POWER OUTPUT	额定电流 RATED CURRENT	效率 EFFICIENCY		
kVA	kVA	kVA	kVA			kg	kgm ²	kW (cosφ=0.8)	A	η(cosφ=0.8)%	η(cosφ=1.0)%	mm
600 r/min (12-pole)												
1563	1469	1360	1250		ZFC7 506-12P	13800	580	1250	82	94.0	95.1	3050X1900X2270
1875	1763	1631	1500		507-12P	14800	670	1500	98	94.3	95.3	3230X1900X2270
2500	2350	2175	2000		ZFC7 564-12P	21500	1340	2000	131	94.6	95.6	3280X2140X2540
3125	2938	2719	2500		565-12P	22000	1640	2500	164	95.0	95.9	3400X2140X2540
4000	3760	3480	3200		566-12P	23000	1900	3200	210	95.5	96.2	3580X2140X2540
5000	4700	4350	4000		ZFC7 634-12P	31000	3460	4000	262	95.4	96.0	3870X2600X2960
6250	5875	5438	5000		635-12P	33500	4460	5000	328	95.7	96.4	3980X2600X2960